



VAW-8

## LOWER BLADE SHAFT FOR A ROLLER CUTTING MACHINE

---

### BACKGROUND OF THE INVENTION

A1 [0001] The invention relates to a lower blade shaft  
5 for a roller cutting machine with at least one lower  
blade for the lengthwise cutting of foils and strips into  
sectors, and a roller cutting machine for the lengthwise  
cutting of foils and strips into sectors.

[0002] Roller cutting machines are used in particular  
10 to cut aluminum foils and strips, but are also used to  
cut composite materials made of aluminum and paper, as  
well as those made of aluminum and plastic, and to cut  
other foils, strips and composite materials in a  
thickness range of several  $\mu\text{m}$  to about one mm. The foils  
15 or strips to be cut can be either bare or lacquered. The  
composite materials to be cut are fabricated via  
lamination or extrusion, for example.

[0003] The lower blade shaft according to the invention or roller cutting machine according to the invention shall be explained in the following based on the example of cutting aluminum foils or strips.

5 Aluminum or aluminum materials are herein understood as alloys containing at least 90% aluminum.

*A1*  
[0004] In order to fabricate aluminum foils and strips, ingots are cast in a first stage in widths between 900 and 2200 mm, hot-rolled, and then cold-rolled  
10 to the final thickness. Depending on the intended use, the aluminum foils and strips are fabricated to varying end thicknesses and widths. In this case, the end thickness is determined via pass reduction in the rolling process. The end width is fabricated via longitudinal  
15 pitching of the strips or foils on so-called roller cutting machines in single or multiple layers.

[0005] A roller cutting machine essentially consists of three structural units:

[0006] 1. an unwind unit, on which the so-called  
20 "parent strip" is unwound;

[0007] 2. a cutting part, in which the parent strip is cut along its length into narrow sectors by blades; and

[0008] 3. a wind unit, in which the previously cut  
25 sectors are wound into rolls.

[0009] This invention also relates in particular to the so-called "shear cutting" procedure. In a shear cutting procedure, the strip or foil is guided over a lower blade shaft with a specific entanglement (i.e., an arrangement of lower blades). An upper blade dipping into the lower blade shaft, e.g., designed either as a razor blade or circular knife cuts the aluminum at a point with a shear or blade cut. The upper blade is pressed against the lower blade by a spring. More recent procedures make use of pneumatic cylinders or diaphragm cylinders instead of a spring.

[0010] During the lengthwise cutting of foils or strips, the cutting widths for the strips to be cut must routinely be adjusted. To this end, the upper blades first have to be adjusted to the new cutting widths, which can be done comparatively easily and quickly. In addition to adjusting the upper blade to the cutting widths, the lower blade must be adjusted to the new cutting widths. For this purpose, the entire lower blade shaft must be replaced in the known roller cutting machines, in order to incorporate a lower blade shaft with lower blades arranged in positions on the lower blade shaft that correspond to the new cutting widths. To this end, adapters are arranged on the lower blade shaft between the lower blades to establish the necessary

distances. This gives rise to a considerable setup period, and hence high costs.

#### SUMMARY OF THE INVENTION

AI [0011] Proceeding from the prior art described above  
5 and the problems associated therewith, the object of this invention is to provide a lower blade shaft or roller cutting machine for which the setup time for altering cutting widths can be significantly reduced.

#### BRIEF DESCRIPTION OF THE DRAWINGS

10 [0012] FIG. 1 is a partial sectional view of a cutting bushing of a lower blade shaft according to the invention;

[0013] FIG. 2a is a sectional view of an embodiment of a lower blade shaft according to the invention showing  
15 the interaction of the lower blade shaft with an upper blade, shown in elevational view, designed as a razor blade;

[0014] FIG. 2b is a sectional view of an embodiment of a lower blade shaft according to the invention showing  
20 the interaction of the lower blade shaft with an upper blade designed as a circular knife; and

[0015] FIG. 3 is a partial sectional view of a lower blade shaft and set upper blades.

DETAILED DESCRIPTION OF THE INVENTION

A1 [0016] The object derived and described above is achieved for a lower blade shaft for a roller cutting machine with at least one lower blade for the lengthwise cutting of foils and strips into sectors by providing a lower blade shaft that has a number of lower blades that exceeds the number of cuts, lower blades that are arranged in essentially regular intervals on the lower blade shaft, and distances between the lower blades that are selected to permit a flexible choice of strip width. The fact that lower blades are arranged on the lower blade shaft in such a way as to enable flexible selection of the widths of the sectors to be cut ensures that the roller cutting machine can be adjusted to different cutting widths without downtimes for conversion work on the lower blade shaft. Only the significantly easier to handle upper blades need to be positioned suitably relative to the lower blades to be adjusted to the altered cutting width, so that the next cutting batch can be fabricated with the desired altered cutting widths. The considerably reduced setup times result in a significantly higher utilization of the machine run time, which in turn leads to clearly reduced costs for the cutting process.

[0017] The distance between the lower blades arranged on a lower blade shaft according to the invention can be reduced by designing the lower blades to alternate between lower blades for making left and right cuts. A  
5 reduced distance between the lower blades ensures a more flexible adaptation to the desired cutting widths.

AI [0018] The lower blades can be arranged to alternate between left and right cuts in a particularly suitable manner by designing the lower blades to have dual cutting  
10 edges on the tongue of a keyway-tongue portion of the lower blade shaft.

[0019] Because the lower blade shaft has numerous cutting bushings in another embodiment of the lower blade shaft according to the invention, and the cutting  
15 bushings each have numerous lower blades, the entire lower blade shaft need not be changed out if the lower blades become worn in specific areas of the lower blade shaft. In a lower blade shaft designed in this way, the cutting bushings that show a particularly high level of  
20 wear can be exchanged, while those cutting bushings that show less or no wear can continue to be used.

[0020] In order to ensure as much flexibility in the setting of the cutting widths as possible, it makes sense for the lower blades to be arranged at a distance of  
25 about 0.5 to 10 mm from each other. It is particularly

advantageous to arrange (divide) the cutting edges at a distance of about 0.8 to 2 mm relative to each other.

[0021] In particular, when cutting aluminum foils, it makes sense, due to the possible pressing of the lower  
5 blade shaft profile onto the aluminum foil to be cut, to hold the keyway widths as small as possible. A keyway width of 0.8 to 2 mm has proven to be particularly suitable with respect to effecting a slight pressing of the profile onto the aluminum foil, while providing  
10 sufficient space for inserting an upper blade.

[0022] Finally, the object derived and described above is achieved by providing a roller cutting machine, for the lengthwise slitting of foils and strips into sectors, having a lower blade shaft according to the invention and  
15 at least two upper blades that insert into the lower blade shaft.

[0023] An embodiment of the invention includes a lower blade shaft for a roller cutting machine for the lengthwise cutting of foils and strips into sectors with  
20 at least one lower blade (3), characterized in that the lower blade shaft has a number of lower blades (3) exceeding the number of cuts, the lower blades (3) are arranged in essentially regular intervals on the lower blade shaft, and the distances between the lower

blades (3) are selected to permit a flexible choice of sector width.

[0024] There are numerous ways to advantageously configure and further develop the lower blade shaft and  
5 the roller cutting machine according to the invention. To this end, for example, reference is made to the following:

[0025] The lower blades (3) may be designed to alternate between lower blades for making left and right  
10 cuts. The lower blades (3) may be designed to have dual cutting edges (4,5) on the tongue (6) of a keyway-tongue division of (2) the lower blade shaft. The lower blade shaft may have numerous cutting bushings (1) each having numerous lower blades. The lower blades (3) may be  
15 arranged a distance of about 0.5 mm to 10 mm from each other. The lower blades (3) may be arranged a distance of about 1 mm to 2 mm from each other. The keyways (7) may have a width of 0.8 mm to 2 mm. The roller cutting machine may have at least two upper blades that insert  
20 into the lower blade shaft.

[0026] Reference is also made to the description of a preferred embodiment in conjunction with FIGS. 1-3.

[0027] The cutting bushing 1 of a lower blade shaft shown in FIG. 1 includes a hollow cylinder roughly 10 cm  
25 long, on which numerous lower blades 3 are arranged on



the outer cylinder surface in a keyway-tongue portion 2. As clearly evident from FIG. 2a and FIG. 2b, the lower blades 3 are here designed as dual cutting edges 4, 5 on the tongue 6 of the keyway-tongue portion 2.

5 [0028] The distance between the cutting edges 4, 5 measures about 0.8 mm via the keyways 7, and about 1.2 mm via the tongues 6 in the embodiment shown.

[0029] In the embodiment shown in FIG. 2a, an upper blade 8 is designed as the upper blade of a razor blade  
10 cutting system. Accordingly, a razor blade 9 moves into a position near the lower blade 3 within a keyway 7.

[0030] FIG. 2b shows the placement of a circular knife 10, as an upper blade, into a position near the lower blades 3 in a shear cutting system. FIG. 2b also  
15 shows that the cutting edges 4, 5 have a cutting angle of about 3°.

[0031] In the embodiment of a lower blade shaft according to the invention shown in FIG. 2, the tongues 6 have a height of about 2 mm.

20 [0032] FIG. 3 shows an embodiment of a lower blade shaft 11 built into a roller cutting machine not shown in detail. In the razor blade cutting system shown in FIG. 3, three upper blades 8 may be placed adjacent three of the roughly one thousand five hundred lower blades  
25 arranged on the lower blade shaft 11. The upper blades 8

are here guided by means of upper blade adjusting equipment 12.

Al. [0033] As is particularly evident from FIG. 3, any cutting width can be set by simply shifting the upper  
5 blade adjusting equipment 12, relative to lower blade shaft 11 according to the invention, along the modular dimension defined by the distances between the cutting edges.

---